

DS-K1T671 Series MinMoe Terminal

Release Notes (2022-02-14)

Device Model: DS-K1T671M/MF DS-K1T671TMW/TMFW Naming Rule: M for M1 card, W for WIFI, F for fingerprint	Firmware Version	ARM: ACS_671_AI3_EN_STD_V3.2.0_build211129 ACS_671_AI3_EN_NEU_V3.2.0_build211129
	SDK	Latest version
	iVMS-4200 Version	Latest baseline

Reason of Upgrade

Fix bugs, enhance products quality and meet customers' requirements.

Modified Features

1. Fix the issue that the device events exceeds the capability set and the automatic deletion cannot be fully covered;

DS-K1T671 Series MinMoe Terminal

Release Notes (2021-11-15)

Device Model: DS-K1T671M/MF DS-K1T671TMW/TMFW Naming Rule: M for M1 card, W for WIFI, F for fingerprint	Firmware Version	ARM: ACS_671_AI3_EN_STD_V3.2.0_build211110 ACS_671_AI3_EN_NEU_V3.2.0_build211110
	SDK	Latest version
	iVMS-4200 Version	Latest baseline

Reason of Upgrade

Fix bugs, enhance products quality and meet customers' requirements.

Modified Features

1. Fix the device offline issue caused by searching device event from iVMS4200 client through ISUP5.0 protocol;
2. Fixed some issues about ISAPI protocol.
3. Optimize the connection with HikCentral Professional platform;
4. For model support fingerprint (-F), it will return quality score results when collecting

fingerprints remotely from platform;

DS-K1T671 Series MinMoe Terminal

Release Notes (2021-09-09)



Device Model: DS-K1T671M/MF DS-K1T671TMW/TMFW Naming Rule: M for M1 card, W for WIFI, F for fingerprint	Firmware Version	ARM: ACS_671_AI3_EN_ STD _V3.2.0_build210731 ACS_671_AI3_EN_ NEU _V3.2.0_build210731
	SDK	Latest version
	iVMS-4200 Version	Latest baseline

Reason of Upgrade

Add new function, fix bugs, enhance products quality and meet customers' requirements.


New Features

1. Add Hik-Connect menu in device UI Menu→Comm. The function is disabled in default.



Modified Features

1. Optimize the wake-up distance of the device screen through the face, and the wake-up distance is consistent with the recognition distance



DS-K1T671 Series MinMoe Terminal Release Notes (2021-06-24)

Device Model: DS-K1T671M/MF DS-K1T671TMW/TMFW Naming Rule: M for M1 card, W for WIFI, F for fingerprint	Firmware Version	ARM: ACS_671_AI3_EN_STD_V3.2.0_build210609 ACS_671_AI3_EN_NEU_V3.2.0_build210609
	SDK	Latest version
	iVMS-4200 Version	Latest baseline

Reason of Upgrade

Fix bugs, enhance products quality and meet customers' requirements.

Modified Features

1. Optimize the function of exporting data to U disk.
2. Optimize the working mechanism of infrared fill light
3. uboot security update

DS-K1T671 Series MinMoe Terminal

Release Notes (2021-02-08)

Device Model: DS-K1T671M/MF DS-K1T671TMW/TMFW Naming Rule: M for M1 card, W for WIFI, F for fingerprint	Firmware Version	ARM: ACS_671_AI3_EN_ STD _V3.2.0_build210203 ACS_671_AI3_EN_ NEU _V3.2.0_build210203 MCU: ACS_DS-K1T671_ST1_GML_GM_V1.0.1_build210104
	SDK	Latest version
	iVMS-4200 Version	Latest baseline

Reason of Upgrade

Add new features, fix bugs, enhance products quality and meet customers' requirements.

New Feature


1. Support https feature

The screenshot displays the 'Configuration' tab in the iVMS-4200 interface, specifically the 'Certificate Management' sub-tab. The left sidebar shows the 'Security' menu item selected. The main content area is divided into four sections for managing certificates:


- Certificate Files:** Includes a 'Certificate Type' dropdown set to 'HTTPS', a 'Create Certificate' button, and a status 'No file.'.
- Import Passwords:** Includes a 'Certificate Type' dropdown set to 'SYSLOG', an 'Upload Certificate' button with a file icon, and an 'Install' button.
- Import Communication Certificate:** Includes a 'Certificate Type' dropdown set to 'SYSLOG', an 'Upload Certificate' button with a file icon, and an 'Install' button.
- Import CA Certificate:** Includes a 'Custom ID' text input field, an 'Upload Certificate' button with a file icon, and an 'Install' button.

2. Support English, Spanish (South American), Arabic, Thai, Indonesian, Russian, Vietnamese, **Brazilian Portuguese**
3. Add Hik-ProConnect platform docking


4. Add advertisement mode, after enable, the wallpaper will be fixed to be displayed on the top of main interface.



5. Add device operation log query function




6. Add ISAPI event monitoring upload (HTTP listening) function





7. Support PIN code to open the door (disabled in default)

Note: PIN code should be configured from software, iVMS4200 already support, HikCentral Pro will support PIN code configuration in V2.1 expected to be released in June




8. Support unbind device with hik-connect account on SADP tool, local UI and web interface






9. Add beauty function to adjust smooth and whiten parameter.



10. Add help interface to check system module version for technical support (long press for 3s).



11. Add privacy protection, customer can define the privacy related parameter, such as Event Storage Settings, Picture Uploading and Storage, Clear All Pictures in Device


The screenshot shows the Hikvision web interface with the 'Privacy' tab selected under the 'Configuration' menu. The left sidebar lists various system settings, with 'Access Control' highlighted. The main content area is divided into three sections:

- Event Storage Settings:** Features a dropdown menu for 'Event Storage Type' with options: 'Overwriting' (selected), 'Delete Old Events Periodically', and 'Delete Old Events by Specified Time'. A red 'Save' button is located below the dropdown.
- Picture Uploading and Storage:** Contains five toggle switches, all of which are turned on:
 - Upload Captured Picture When Authenticating
 - Save Captured Picture When Authenticating
 - Save Registered Picture
 - Upload Picture After Linked Capture
 - Save Pictures After Linked Capture
 A red 'Save' button is positioned below these toggles.
- Clear All Pictures in Device:** Includes two checkboxes:
 - Clear Registered Face Pictures
 - Clear Captured Pictures
 A pink 'Clear' button is located at the bottom of this section.


12. Configure the time period when the white light fill light is turned on and off in device local menu or web interface

The screenshot displays the 'Display Settings' page in the Hikvision web interface. A green notification banner at the top indicates 'Save succeeded.' The page is divided into several sections:

- Display Settings:** Includes dropdown menus for 'Video Standard' (set to PAL(50HZ)) and 'WDR' (set to Disable).
- Basic Parameter:** Features a large grayscale image of a person's face.
- Image Adjustment:** Contains a sub-section for 'Supplement Light Parameters' which is highlighted with a red box. This section includes:
 - 'Supplement Light Type' set to 'Supplement Light'.
 - 'Supplement Light Mode' set to 'Schedule'.
 - 'LED Light Brightness' set to 0.
 - 'Start Time' set to 00:00:00.
 - 'End Time' set to 23:59:59.




13. Add audio prompt 'The door is open' when open door on iVMS4200, HikCentral Pro, Hik-Connect App, and device UI will show prompt




Modified Features


4. Hik-Connect function is turned off in default for privacy protection, if customer want to manage device from App, please turn on manually in the web.




5. The face matching algorithm is upgraded. Improve the speed and accuracy of face recognition. Improved the recognition effect of dark masks
6. DNS can be configured from device UI in menu → Comm. → Wired Network



7. Optimized the ISUP and Hik-Connect event upload mechanism.
8. Add stranger authentication timeout time configuration



9. Add advertisement/wallpaper play schedule configuration, slide show interval.



10. Optimize the firmware upgrade mechanism to ensure possible problems caused by power outage during the upgrade process.

Customer Impact and Recommended Action

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action. For any questions and request for this firmware, please contact our local technical support team.

Note:

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain errors known as errata, which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd.
No. 555 Qianmo Road, Binjiang District, Hangzhou 310051, China
Tel: +86-571-8807-5998
FAX: +86-571-8993-5635
Email: overseabusiness@hikvision.com