

63xx Fisheye Camera Firmware Version: V5.4.5

Release Note (External) (2017-02-24)

Firmware Basic Information	Firmware Version:	V5.4.5 build170206
	SDK Version:	V5.1.6.30
	Play Library (PlayCtrl.dll)	V7.3.2.76
	Encapsulation Library (SystemTransform.dll)	V2.5.1.13
	Web version	V4.0.1 build170118
	Smart configuration library	V4.1.8.1
	iVMS-4200	Version 4200 V2.02.15.106
		build20160702
	Heat Map algorithm library	V1.0
	version	

Compatibility Update

• NUUO:

Version: V6.4.0, drive version: V4.15

• Milestone:

1. Milestone Enterprise 8.1a(10.1a), Milestone Corporate 10.2a

2. Milestone Corporate 10.1a, Milestone drive version: Device Pack 8.6

Avigilon:

Avigilon Control Center: V5.8.4.16

• Excaqvision:

Version: 7.8.2.98464

Genetec Omnicast:

Version: 4.8 SR8

Security Center:

Version: 5.5 SR1

28181:



V1.0.0.1/V1.0.0.5

Network keyboard:

DS-1100K V2.4.0 build150827

• Series port keyboard:

DS-1004K V1.2.0

Official Tested ONVIF:

V1601

NVR/DVR accessing version:

- 1. Marvell E series: DS-96128N-E16 (V3.0.4_150616) (This series NVRs has been discontinued and the future version will not test)
- 2. Marvell F series: DS-96128N-F16 (V3.2.6 160411)
- 3. Hisi3535 E series: DS-7732N-E4/16P (V3.4.80)
- 4. Hisi3535 G series: DS-7608N-G2/4P (V3.4.1 build 151225)
- 5. Hisi3798 K1 series: DS-7816N-K1 (V3.4.80)
- 6. Hisi3536 I8 series: DS-8664N-I8 (DS-7632N-I2/16P)
- 7. Hisi3536 K series: V3.4.80
- 8. Hisi3520D\3521: DS-7608N-SHT (V3.0.17_150804)
- 9. Netra DVR: DS-9016HF-ST (V3.4.2 build160129)
- 10. 8107 plat: DS-7616N-SE (V3.0.15_150528)
- 11. Hisi plat F series: DS-9664N-F8/I (V3.3.4_150715)
- 12. Channel NVR: DS-7832N-K2 (V3.3.9_151228)
- 13. 96000N-I series: V3.6.0

63xx Fisheye Camera Firmware V5.4.14 build160427 Features

1. New Features

Support 29 languages in web browser: Traditional Chinese, English, Russian, Turkish, Japanese,
Korean, Thai, Vietnamese, Estonian, Bulgarian, Hungarian, Czech, Slovak, French, Italian, German,
Spanish, Portuguese, Polish, Greek, Dutch, Romanian, Finnish, Norwegian, Danish, Swedish,
Croatian, Serbian, Slovenian.

2. Optimization

- Remove the IP Server and HiDDNS in the web interface
- Support 4 lines text overlay for the first channel under hardware dewarpping mode.
- Solve the issue that PTZ images cannot be moved to the edge when zooming in/out under



hardware and software dewarpping modes.

• The neutral device won't display the model information when the customized model is empty.

Customer Impact and Recommended Action

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action. For any questions and request for this firmware, please contact our local technical support team.

Remarks:

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd.

No. 555 Qianmo Road, Binjiang District, Hangzhou 310051, China

Tel: +86-571-8807-5998 FAX: +86-571-8993-5635

Email: overseabusiness@hikvision.com



Supported Product List (63X2)			
Product Category	Model Number	Product Description	
Fisheye Camera	DS-2CD6332FWD-I(V)(1.19mm)(NEU)(O1)	3MP, WDR, 360° view angle	
Fisheye Camera	DS-2CD6332FWD-I(V)(S)(1.19mm)(STD/NEU)	3MP, WDR, 360° view angle	
Fisheye Camera	DS-2CD6362F-I(V)(S)(1.27mm) (STD/NEU)	6MP, 360° view angle	
Fisheye Camera	DS-2CD63C2F-I(V)(S)(2mm) (STD/NEU)	12MP, 360° view angle	
Fisheye Camera	DS-2CD63C2F-I(V)(S)(2mm) (NEU)(O1)	12MP, 360° view angle	