2020-10106 page 1 of 7

No: 2020-10106











TEST

REPORT

Equipment under Test: NETWORK CAMERA

Model Number DS-2XM6122G0-IDM

Manufacturer: Hangzhou Hikvision Digital Technology Co., Ltd.

National Computer Peripheral Equipment Quality

Supervising Test Center

2020-10106 page 2 of 7

National Computer Peripheral Equipment Quality Supervising Test Center

Test Report

No:2020-10106

			8	
Product	NETWORK CAMERA	Model type	DS-2XM6122G0-IDM	
Product		Trademark	HIKVISION	
Entrusted By	Hangzhou Hikvision Digital Technology Co., Ltd.	Testing Type	Entrustment	
Manufacturer	Hangzhou Hikvision Digital Technology Co., Ltd.	Sample Class	·——	
Sample Origin	Delivered	Delivery Date	2020-03-09	
Sample Number	One set	Delivered by	Fu Meixia	
Sample Radix		Manufacture Date		
Test Standards	IEC 60529:1989+AMD1:1999+AMD enclosures(IP Co	4	of protection provided by	
Test Items	IP Code 67 test of protection			
	This test proved that the DS	S-2XM6122G0-ID	M NETWORK CAMERA	
Test Result	manufactured by Hangzhou Hikvisio the Test Standard.	(F)	ogy Co., Ltd. complied with	
Test Result Remark	· O ₂	DS-2CD6520D-IO and the test DS-2 d nameplate differsponsible for this	DS-2CD6520D-I 2XM6122G0-IDM erences, won't affect IP statement.	



2020-10106 page 3 of 7

Test Site	National Computer Peripheral Equipment Quality Supervising Test Center					
Test Date	2020-03-12~2020-03-14					
	S/N	Description	Model	No.	Cal due	
	1	IP water proof testing system	HY-IPX1-6	SB116	2020-07-14	
Main	2	Dust test chamber	SC-500	HJ0083	2020-12-09	
Testing Equipments and		. 0171				
Instruments		,5	X	护		
	Vic	7	350			
A R		_3	5-			
17º		A TOPE				
Sample Number	1#: D71033418					
	AHE HELD					
		: 51011	X.	Y		
Distribution Of Sample	1#: IP Gode 67 test of protection Climatic conditions:					
8						
13-			//			
Remark						
	Ambient temperature: 22~23°C Relative humidity: 45~47%					
	Atmospheric pressure: 101~102kPa					
	~1 [^]	, \$ ×				
Ď	Hir	7				
AR	J					

2020-10106 page 4 of 7

Test Items	Items Technical specifications	
IP6X	Dust-tight, No ingress of dust. The test is performed using a dust chamber. The talcum powder used shall be able to pass through a square-meshed sieve the nominal wire diameter of which is 50 µm and the nominal width of a gap between wires 75 µm. The amount of talcum powder to be used is 2 kg per cubic metre of the test chamber volume. Duration of test: 8 hours. After the test, the inside of EUT should be no dust.	Pass
IPX7	Diving tests for a short time, No ingress of water. -The test is made using a water tank. -Temperature of the water tank: $20^{\circ}C \pm 2^{\circ}C$ -Samples from the bottom of the water: 1000 mm -Duration of test: 30 minutes After the test, the inside of EUT should be no water.	Pass
Remark	OILIE FER	
	ng Minkang Wang Jue	
A PE		





2020-10106 page 5 of 7

EUT picture





HIKVISION

IR NETWORK CAMERA

Model: DS-2XM6122G0-IDM Amm

I/P: 24V==TBDA,TBDW

SN.: D71033418

SV: V5.5.84_190801

MAC: 84:9A:40:A2:54:E2 CAN ICES-3(B)/NMB-3(B) 10/2019

(B) Made in China





2020-10106 page 6 of 7





A BELLIA

NOTES

1. Reports with no signet of "test report or that of the inspect institute are all invalid

- 2. Partial copy of this report is forbidden. Entire copy of the report without signet is invalid.
- 3. Report with no approval are invalid.
- 4. Altered report is invalid.
- 5. If any disagreement on this report, a written claim is requested to be submit to the institute within 15days on receipt of the report.
- 6. Generally, authorized inspection is only responsible for the JIKV151011#EFF samples inspected.

Address: 316#, Jiang Hong South Road, Hangzhou, China

Tel: +86 571 88366861 Fax: +86 571 88366821

P.O.Box: 1215#, Hangzhou, China

Zip Code: 310052

A RELITIES TO THE E-mail: wangwx@ksign.cn

WEB: www.ksign.cn