

## DS-M5504HNI/M12 Series Mobile Video Recorder



### Key Feature

- User-friendly GUI providing easy and flexible operations.
- 3G (WCDMA) and Wi-Fi module providing flexible data transmission solutions.
- Pluggable GPS (Global Positioning System) module precisely positioning the vehicle via the satellite and recording the location information in the video stream.
- Hikvision private protocol (4000 protocol) and ONVIF supported.
- 4 M12 independent network interfaces connectable to 4 IP cameras; each channel supports up to 1080P resolution with H.264 encoding technology.
- Pluggable dummy HDD for HDD with up to 2 TB capacity.
- Stores videos on SD card when HDDs/SSDs are broken.
- Information collection interfaces collect driving information such as left/right turn, braking, reversing, etc.
- Software-based firewall supported.
- Support accessing via WEB browser.
- Wide-range power input (9 to 32 VDC).
- Shutdown delay (0 h to 6 h) and 24-hour scheduled startup/shutdown.
- Power-off protection prevents key data from loss.
- Aluminum die-cast chassis of good heat dissipation performance with no fan design which well adapts to working environment.
- Dummy HDD with USB interface supports intelligent temperature control and data export.

### Available Model

DS-M5504HNI/GW/WI(M12), supporting 3G dialing and Wi-Fi




## Specifications

Model		DS-M5504HNI/M12
Video/Audio Input	IP Camera	4
	Two-way Audio	1, integrated in EXT.DEV interface
Video/Audio Output	Video Output	CVBS: 2, PAL: 704 × 576, NTSC: 704 × 480 VGA: 1, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
	Audio Output	2
Encoding/Decoding Parameters	Video Compression	H.264
	Encoding Resolution	Main stream: 1080p/720p/WD1/4CIF. Sub-stream: 4CIF/2CIF/CIF
	Frame Rate	PAL: 1 to 25fps, NTSC: 1 to 30fps;
	Audio Compression	G.711
	Stream Type	Video, Video & Audio
	Audio Bitrate	16 Kbps
	Dual Stream	Supported
Storage	HDD/SSD	2 × 2.5 inch HDD/SSD, up to 2 TB for each HDD/SSD A dummy HDD with USB 3.0 interface
	SD Card	1 × SD card, up to 256 GB
Wireless Network	3G/4G Dialing	1 × 3G/4G card slot, 1 × SMA antenna
	Wi-Fi	1 × 2.4 G Wi-Fi SMA antenna
Positioning	GNSS (Global Navigation Satellite System)	GPS (Global Positioning System), 1 × SMA antenna
PoE	PoE Interface	4 × M12 PoE interfaces
	Max. Consumption	30 W (in total)
External Interface	Network Interface	1 × 10M/100M RJ45 Ethernet interface
	Serial Port	1 × RS-232, 1 × RS-422
	USB Interface	<ul style="list-style-type: none"> <li>Front panel: 1 × USB 2.0</li> <li>Rear panel: 1 × USB of 5-pin aviation plug</li> </ul>
	Sensor-in	4 high/low level signal inputs
	Alarm Input	3 high/low level signal inputs, 1 pulse signal input (reserved)
	Alarm Output	2 relay signal outputs
General	Operating Method	Mouse, IR remote control, Web control
	Power Supply	9 to 32 VDC
	Consumption	<ul style="list-style-type: none"> <li>Standby: ≤ 0.5 W</li> <li>Full load: ≤ 70 W</li> </ul> Note: Without peripheral and storage media: ≤ 20 W
	Working Temperature	<ul style="list-style-type: none"> <li>Device that provides dummy HDD with heating function: -30 °C to +60 °C (-22 °F to +140°F)</li> <li>Other devices: -10 °C to +60 °C (14 °F to 140°F)</li> </ul>
	Working Humidity	10% to 90%
	Dimensions (W × D × H)	206 × 208.6 × 60 mm (8.1 × 8.2 × 2.4 inch)
	Weight (Without Storage Media)	1.6 kg (3.53 lb)


## Physical Interfaces

### Front Panel













No.	Name	No.	Name
1	LAN Network Interface	4	Indicators
2	USB Interface	5	Dummy HDD
3	Hard Disk Lock	6	SD Card Slot




### Rear Panel




No.	Name	No.	Name
1	PoE 1 to PoE 4 Interfaces ( M12 Connector)	6	VGA Interface
2	RS-232 Interface	7	EXT. DEV (including audio output, two-way audio and RS-422)
3	USB Interface	8	I/O (including alarm in, alarm out and sensor in)
4	AV OUT	9	Pluggable Module (including 3G Wi-Fi and GPS)
5	Power Supply		

## Packing List

Description	Quantity	Picture	Note
Fuse	2		
Power cord	1		
Aviation plug-to-BNC cable	1		
Key	1		
Remote control	1		
Alarm line	1		
Serial port line	1		
Extension cable	1		
Screwdriver	1		
3G antenna	1		For GW model.

Description	Quantity	Picture	Note
4G antenna	1		For GLF model.
Wi-Fi antenna	1		For WI model.
GPS antenna	1		For model with GPS module.

## Peripheral Connection



Distributed by

## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-[0]31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com