

AE-VC061P-ITS IR Dome Vehicle-Mounted Camera

Key Feature


- Clear image with high resolution
- Low illumination, 0.1 lux @ (F1.2, AGC ON), 0 lux with IR
- Supports auto electronic day & night switch
- Adopts dual-lens to monitor more scenes
- Adopts electronic shutter to adapt to different environment
- Supports auto gain control, self-adaption to light
- Built-in MIC, supports audio input
- Advanced industrial design with high reliability
- Adapts shock-proof design and aviation plug



Available Model

AE-VC061P-ITS

Dimension



Specification

Camera	
Image Sensor	Progressive Scan CMOS
Video Standard	PAL
Min. Illumination	0.1 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/25 s to 1/50,000 s
FOV	Front lens 2.1 mm, horizontal FOV 121°, vertical FOV 67°, diagonal FOV 137° 2.8 mm, horizontal FOV 79°, vertical FOV 42°, diagonal FOV 92° Rear lens 2.1 mm, horizontal FOV 121°, vertical FOV 67°, diagonal FOV 137° 2.8 mm, horizontal FOV 79°, vertical FOV 42°, diagonal FOV 92°
Lens Mount	M12
Angle	Front lens Bracket rotate: 0 to 90° Rear lens Horizontal: 0 to 360°, vertical: 0 to 60°, rotate: 0 to 360°
Day & Night	Front lens, no Rear lens, electronic
Horizontal Resolution	700 TVL
Synchronization	Internal
S/N Ratio	42 dB
Interface	
Video Output	2, Vp-p Composite Output (aviation plug)
Audio Input	Build-in MIC
Audio Output	2, aviation plug (linear resistance: 1 kΩ)
Aviation Pin Order	Hikvision, 1: Video; 2: Audio, 3:Power, 4: Grounding Others, 1: Power; 2: Grounding, 3:Audio, 4: Video
General	
Working Temperature	-40°C to 75° C (-40 °F to 167 °F)
Working Humidity	≤ 90%
Power Supply	9 to 16 VDC
Power Consumption	Front lens: Max. 1.2 W Rear lens: Max. 2.2 W
IR Distance	10 m
Dimension	59.9 mm × 85.6 mm × 80 mm (2.36" × 3.37" × 3.15")
Weight	200 g (0.44 lb)

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com