

How to Add Wireless Detector to AX PRO Wireless Control Panel

Title:	How to Add Wireless Detector to AX PRO	Version:	v1.0	Date:	09/07/2020
	wireless Control Panel				
Product:	DS-PWA Series AX PRO Wireless	Page:	1 of 2		

Preparation

- 1. DS-PWA Series AX PRO Wireless Security Control Panel
- 2. Wireless Detector DS-PDPC12P-EG2-WE
- 3. IE explorer and App Hik-Connect

How to Add Wireless Detector to AX PRO Wireless Control Panel

For AX PRO Panel, You can use Login AX PRO Hik-Conenct interface to add detector (Scan the detector QR code) or enable Enrollment Mode , or login IE Browser

with Hik-Connect account and password, then enable Enrollment Mode.

1. Use Hik Connect APP QR Add Function

- 1) Add the AX PRO to Hik-connect at first
- 2) Login AX PRO, select Device and click \oplus , scan the QR code and follow the steps.



2. Use Hik Connect APP Enrollment Function

- 1) Add the AX PRO to Hik-connect at first
- 2) Login AX PRO, select Device and click •, select System Options---Enrollment Mode, and Enable Enrollment Mode.

<	AX PRO	< 0	< Settings	System Options
	0		AX PRO Device Model: DS-PWA96-M-WE Serial No.:002046845 Device Version: V1.2.1 build 200918	Panel Fault Check Arm Options Enrollment Mode
	Ū		S User Management	
Area	Device	Status	🖄 System	~
Area 1 Disarm			Configuration System Options	
			Network Camera	>
	•		습 Area	
			(ဖု) Communication Parameters	Enter the Enrollment Mode
			X Maintenance	>
			🔶 Configure Wi-Fi Network	>
↑ ¢	û	٥	Authorize Delete Device	>

3) Turn on the power switch of Detector.

ſ)
ŀ	E	_	╡	1
	ł		5	
	2 1	ś		1

4) Check the status of Detector

<	AX PRO	< 0
	0	
	U	
Area	Device	Status
	All Areas 👻	
	Wireless Zone 1 Area 1 11 💼	
	Keyfob 1	
	•	

3. Use AX Pro Brower Enrollment Function

- 1) Add the AX PRO to Hik-connect at first
- 2) Use Brower Login Panel IP, account and password is Hik-Connect account and password.

\leftarrow \rightarrow \bigcirc \bigcirc 10.896550 checkpaper(no)inamp	
HIKVISION	
vesaey_hc ↓ vesaey_hc ↓ ······· Logn	

©2020 Hikvision Digital Technology Co., Ltd. All Rights Reserved.

3) Select System—System Options—Device Enroll Mode, enable Enter the Enrollment Mode

HI	KVISION					
₽.	Overview	System Management	Schedule & Timer	Panel Fault Check	Arm Options	Device Enroll Mode
2	User					
***	System	Wireless	Device Enrollment M	ode	Enter the Enr	ollment Mode
System Settings						
	System Options					
	System Security					
	Device					
	Area					
(ini)	Communication					
ŝ	Maintenance					

4) Turn on the power switch of Detector.



5) After finish adding, click Exit the Enrollment Mode to exit.



HI	KVISION							
2	Overview	AX PRO S	Status Zone Status	Sounder Status A	utomation Repe	eater Status Tag	Reader Status	Keypad Status
2	User							
	System	C Refree	₿ Refresh					
	Device	Zone	Name	Temperature	Battery Status	Signal Strength	Alarm Status	Status
	Area	1	Wireless Zone 1	25	100%	(Strong)	Normal	Disarm
(m)	Communication							
ŝ	Maintenance							
	Device Information							
	Device Status							
	Log							
	Device Maintenance							

6) Check the Detector Status: Maintenance—Device Status—Zone Status

