


No 2013-3925-1



TEST REPORT

Equipment under Test: Camera

Model Number: DS-2CD2512XYZ-ABCD

Manufacturer: Hangzhou Hikvision Digital Technology Co., Ltd.

Test Standards: EN 50155:2007

Results: PASS

Date of issues: 2013-11-20

NATIONAL COMPUTER PERIPHERAL EQUIPMENT
QUALITY SUPERVISING TEST CENTRE




VERIFICATION OF COMPLIANCE

Equipment under Test:	Camera
Trade Name:	N/A
Model Number:	DS-2CD2512XYZ-ABCD
Serial Number:	N/A
Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd.
Manufacturer:	Hangzhou Hikvision Digital Technology Co., Ltd.
Type of Test:	Entrustment Test
Technical Standards:	EN 50155:2007;
Verification Issuing Office Name & Address	National Computer Peripheral Equipment Quality Supervising Test Centre (CPTC) 36# Macheng Road, HangZhou City, Zhejiang Province, China
File Number:	2013-3925-1
Date of test:	2013-10-28 to 2013-11-10
Condition of Test Sample:	Normal


This report shall not be reproduced, except in full, without the written approval of CPTC.

The test results of this report relate only to the tested sample identified in this report.


Approved by:



Checked by:



Chief tester:



Contents

1. GENERAL INFORMATION.....	1
1.1 TEST ITEMS.....	1
1.2 EUT (EQUIPMENT UNDER TEST) INFORMATION	4
1.3 TEST DESCRIPTION	4
1.4 AMBIENT CONDITION FOR TEST	4
1.5 REQUIREMENTS	4
1.6 TEST EQUIPMENT LIST.....	5
2. CONDUCTED EMISSION TEST	7
2.1 TEST STANDARDS	7
2.2 DIAGRAM OF TEST SETUP.....	7
2.3 TEST DESCRIPTION	7
2.4 TEST RESULT	10
3. RADIATED EMISSION TEST	11
3.1 TEST STANDARDS	11
3.2 DIAGRAM OF TEST SETUP.....	11
3.3 TEST EQUIPMENTS USED	11
3.4 TEST DESCRIPTION	11
3.5 TEST RESULT	13
4. ELECTROSTATIC DISCHARGE TEST	14
4.1 TEST STANDARDS	14
4.2 SEVERITY LEVELS AND PERFORMANCE CRITERION	14
4.3 DIAGRAM OF TEST SETUP.....	14
4.4 TEST EQUIPMENTS USED	14
4.5 TEST DESCRIPTION	14
4.6 TEST SETTING	15
4.7 TEST RESULT	15
5. RF FIELD STRENGTH SUSCEPTIBILITY TEST	16
5.1 TEST STANDARDS	16
5.2 SEVERITY LEVELS AND PERFORMANCE CRITERION	16
5.3 DIAGRAM OF TEST SETUP.....	16
5.4 TEST EQUIPMENT USED	16
5.5 TEST DESCRIPTION	16
5.6 TEST SETTING	17
5.7 TEST RESULT	17

6. ELECTRICAL FAST TRANSIENT/BURST TEST	18
6.1 TEST STANDARDS	18
6.2 SEVERITY LEVELS AND PERFORMANCE CRITERION	18
6.3 DIAGRAM OF TEST SETUP	18
6.4 TEST EQUIPMENT USED	19
6.5 TEST DESCRIPTION	19
6.6 TEST SETTING	19
6.7 TEST RESULT	19
7. SURGE TEST	20
7.1 TEST STANDARDS	20
7.2 SEVERITY LEVELS AND PERFORMANCE CRITERION	20
7.3 DIAGRAM OF TEST SETUP	20
7.4 TEST EQUIPMENT USED	20
7.5 TEST DESCRIPTION	20
7.6 TEST SETTING	21
7.7 TEST RESULT	21
8. CONDUCTED SUSCEPTIBILITY TEST	22
8.1 TEST STANDARDS	22
8.2 SEVERITY LEVELS AND PERFORMANCE CRITERION	22
8.3 DIAGRAM OF TEST SETUP	22
8.4 TEST EQUIPMENT USED	22
8.5 TEST DESCRIPTION	22
8.6 TEST SETTING	23
8.7 TEST RESULT	23
9. POWER SUPPLY OVER VOLTAGE	24
9.1 TEST STANDARDS	24
9.2 DIAGRAM OF TEST SETUP	24
9.3 TEST CONFIGURATION AND PROCEDURE	24
9.4 TEST SETTING	24
9.5 TEST RESULT	24
10. VIBRATION TEST	25
10.1 TEST PROCEDURE	26
10.2 ACCEPTANCE CRITERIA	26
10.3 TEST RESULT	26
11. SHOCK TEST	26

11.1 TEST PROCEDURE:	27
11.2 ACCEPTANCE CRITERIA	27
11.3 TEST RESULT	27
12. DRY HEAT TEST.....	27
12.1 TEST PROCEDURES	27
12.2 ACCEPTANCE CRITERIA	27
12.3 TEST SETTING	28
12.4 TEST RESULT	28
13. COOLING TEST.....	28
13.1 TEST PROCEDURES	28
13.2 ACCEPTANCE CRITERIA	28
13.3 TEST SETTING	28
13.4 TEST RESULT	29

1. General Information

All tests that mentioned in this document are according to the test procedure of EN 50155.

1.1 Test Items

No.	Phenomenon	Basic standard	Severity	Performance Criteria ^①	Result
1.	Conducted Emission	EN 50155 12.2.8.2 EN 50121-3-2 table 5 Ref EN 55011 clause 7	9 kHz – 150 kHz: No limit 150 kHz – 500 kHz: 79 dB μ V quasi-peak 500 kHz – 30 MHz: 73 dB μ V quasi-peak	N/A	Pass
2.	Radiated Emission	EN 50155 12.2.8.2 EN 50121-3-2 table 6 Ref EN 55011 clause 7	30 MHz – 230 MHz: 50 dB μ V/m quasi-peak @3m 230 MHz – 1 GHz: 57 dB μ V/m quasi-peak @3m	N/A	Pass
3.	ESD	EN 50155 12.2.7.2 EN50121-3-2 table 9 Ref : IEC 61000-4-2	8 KV air discharge 6 KV Contact discharge	A	Pass
4.	Radio frequency	EN 50155 12.2.8.1 EN 50121-3-2 table 9 Ref : IEC 61000-4-3	Electric Field Strengthen (V/m) in rms : 80 MHz to 1GHz 20V/m 1.4GHz to 2.1GHz 10V/m 2.1GHz to 2.7GHz 5V/m Modulation : 80% AM (1kHz) for all ranges	A	Pass

No.	Phenomenon	Basic standard	Severity	Performance Criteria ^①	Result
5.	Fast Transients bursts	EN50155 12.2.7.3 EN50121-3-2 table 7&8 Ref : IEC 61000-4-4 clause 8	+/-2 kV 5/50 ns Tr/Th 5 kHz repetition frequency	A	Pass
6.	Surges	EN 50155 12.2.7.1 EN50121-3-2 table 7 Ref : IEC 61000-4-5 Clause 8	1.2/50 μ s Open circuit test voltage line to ground: +/- 2KV 42 Ω , 0.5 μ F Open circuit test voltage line to line: +/- 1KV 42 Ω , 0.5 μ F	B	Pass
7.	Conducted radio frequency	EN 50155 12.2.8.1 EN 50121-3-2 table 7&8 Ref : IEC 61000-4-6 Clause 8	10 Vrms (carrier voltage) 150 kHz to 80 MHz 1 kHz, 80% AM	A	Pass
8.	Supply Over Voltage	EN 50155 12.2.6	1.4 Un, d=0.1sec, D=1sec, Rs = 1 Ω +/- 10% Trapezoidal overvoltage according to EN50155 12.2.6 a)	A	Pass
9.	Performance Test	EN 50155 12.2.2	0.7Un-1.25Un	N/A	Pass
10.	Vibration Test	EN 50155 12.2.11 EN 61373 table 1 & 2	Category 2 (Bogie mounted) according to EN 61373 table 1 & 2	N/A	Pass
11.	Shock Test	EN 50155 12.2.11 EN 61373 table 3	Category 2 (Bogie mounted) according to EN 61373 table 3	N/A	Pass

No.	Phenomenon	Basic standard	Severity	Performance Criteria ^①	Result
12.	Dry heat	EN50155 12.2.4 EN60068-2-2 test Bd	70°C, 8h(power on)	N/A	Pass
13.	Cooling test	EN50155 12.2.3 EN60068-2-1 test Ad	-25°C, stay for 2h,then Power on for 8h	N/A	Pass

①Note: Performance Criteria

Criterion A:

The apparatus shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

Criterion B:

After the test, the equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a performance level (or permissible loss of performance) specified by the manufacturer, when the apparatus is used as intended. During the test, degradation of performance is allowed, however. No change of actual operating state or stored data is allowed. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and from what the user may reasonably expect from the apparatus if used as intended.

Criterion C:

Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls, or by any operation specified in the instructions for use.

1.2 EUT (Equipment Under Test) Information

Name: Camera

Test Model No.: DS-2CD2512XYZ-ABCD

Power Supply: DC 12V

1.3 Test Description

1.3.1 Accessories Used

Name	Model	Manufacturer
ADAPTER	BSW0127-1210002W	Aocpower
PC	E47A	Lenovo
PC	Toshiba	PQF75E-AAAA8
PC	Dell	XPSL502X

1.4 Ambient Condition for Test

Item	Required
Temperature (°C)	15~35
Humidity (%RH)	25~75
Barometric Pressure (mbar)	860~1060

1.5 Requirements

1.5.1 EMC test requirements

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the Operating Instructions.

The performance acceptance criteria are defined as: The overall emission level do not exceed the limits.

Immunity: The equipment under test (EUT) was configured to the representative operating mode and conditions.

The performance acceptance criteria are defined as: Meet the Performance Criteria of 1.1.

1.5.2 Environment test requirements

The acceptance criteria are defined as:

- No failure or damage shall occur
- The functional check shall not show any failure or damage nor any results which are beyond the specified tolerance

1.5.3 Requirements for functional check.

The performance acceptance criteria are defined as:

Correct video signal being received and transmitted.

Slight disturbance, flickering or jittering observed on the preview screen is permitted.

1.6 Test Equipment List

For ESD test:

Manufacturer/Type	Model No.	Serial No.	Last Cal.	Cal. Due
Schaffner ESD Generator	NSG438	DC0074	29/05/2013	28/05/2014

For Radiated Electromagnetic Field immunity Measurement:

Manufacturer/Type	Model No.	Serial No.	Last Cal.	Cal. Due
FLUKE /Signal Generator	N5181A	DC0106-3	11/06/2013	10/06/2014
AR/Power Amplifier	AS0102	DC0106-7	N/A	N/A
AR/Power Amplifier	CBA1G	DC0106-9	N/A	N/A
AR/Field probes	HI-6105	DC0106-9	18/04/2013	17/04/2014

For Radiated Emission Measurement:

Manufacturer/Type	Model No.	Serial No.	Last Cal.	Cal. Due
R&S EMI Receiver	ESIB26	DC0065	17/06/2013	16/06/2014
All band antenna	CBL6112A	DC0068	N/A	N/A
Anechoic chamber	966	SB053	N/A	N/A

For Conducted Emission Measurement:

Manufacturer/Type	Model No.	Serial No.	Last Cal.	Cal. Due
R&S EMI Receiver	ESIB26	DC0065	17/06/2013	16/06/2014
Line Impedance Stabilization Network	ESH3-Z5	DC0067	N/A	N/A

For Fast Transients/Burst test:

Manufacturer/Type	Model No.	Serial No.	Last Cal.	Cal. Due
Schaffner Fast Transients /Burst Generator	NSG2025	DC0071	25/06/2013	24/06/2014

For immunity to Conducted Disturbance /Induced by Radio-Frequency Field :

Manufacturer/Type	Model No.	Serial No.	Last Cal.	Cal. Due
-------------------	-----------	------------	-----------	----------

SCHAFFNER/RF Generator	NSG2070	DC0070	24/09/2013	23/10/2014
SCHAFFNER /CDN M3	CDN-M316	15864	24/09/2013	23/10/2014
SCHAFFNER /CDN M2	CDN-M216	12761	24/09/2013	23/10/2014

For Surge/ Voltage Dips/ Short Interruption and Voltage Variation Immunity test:

Manufacturer/Type	Model No.	Serial No.	Last Cal.	Cal. Due
SCHAFFNER/Surge /Dips/Interruption and Variations Simulator	NSG2050	DC0011	16/04/2013	15/04/2014

For Cooling/Dry Heat test

Manufacturer/Type	Model No.	Serial No.	Last Cal.	Cal. Due
Temperature & Humidity Chamber	THS-D7C	SB055	07/12/2013	06/12/2013

For Vibration, Shock, and Bump test


Manufacturer/Type	Model No.	Serial No.	Last Cal.	Cal. Due
Vibration	DCS-1000-10-05	SB077	11/06/2013	10/06/2014
Shock and Bump	SB-200	SB112	19/05/2013	18/05/2014

2. Conducted Emission Test

2.1 Test Standards

EN 55011 clause 7

2.2 Diagram of Test Setup




2.3 Test Description

2.3.1 Configuration of Instruments

Test Equipments Used

EQP. Description
LISN: Line Impedance Stabilization Network
R&S EMI Receiver

Test Receiver Setting



Detector: Quasi-Peak and Average

Band Width: 9KHz

Frequency Range: 150KHz to 30MHz

Reported Emission:

Power-L

EUT: DS-2CD2512XYZ-ABCD

Manufacturer:

Operating Condition:

Test Site: Lab 52 EMC Chamber (3)


Operator: Huang damping

Test Specification:

Comment:

SCAN TABLE: "EN 50121-3-2 V fin"

Start	Stop	Step	Detector	Meas.	IF	Transducer
Frequency	Frequency	Width		Time	Bandw.	
10.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	None
150.0 kHz	30.0 MHz	4.0 kHz	QuasiPeak	1.0 s	9 kHz	None



MEASUREMENT RESULT: "3925-1L_fin QP"

10/28/13 9:07PM

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dB μ V		dB	dB μ V	dB	
24.546000	32.60	11.2	73	40.4	L1	GND
28.210000	37.20	11.4	73	35.8	L1	GND
28.518000	36.30	11.4	73	36.7	L1	GND
29.006000	32.80	11.4	73	40.2	L1	GND
29.126000	33.90	11.4	73	39.1	L1	GND
29.986000	36.60	11.5	73	36.4	L1	GND

Power-N

EUT: DS-2CD2512XYZ-ABCD

Manufacturer:

Operating Condition:

Test Site: Lab 52 EMC Chamber (3)


Operator: Huang damping

Test Specification:

Comment:

SCAN TABLE: "EN 50121-3-2 V fin"

Start	Stop	Step	Detector	Meas.	IF	Transducer
Frequency	Frequency	Width		Time	Bandw.	
10.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	None
150.0 kHz	30.0 MHz	4.0 kHz	QuasiPeak	1.0 s	9 kHz	None



MEASUREMENT RESULT: "3925-1N_fin QP"

10/28/13 9:04PM

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBμV		dB	dBμV	dB	
0.454000	46.80	10.0	79	32.2	N	GND
25.342000	34.80	11.2	73	38.2	N	GND
27.294000	34.90	11.3	73	38.1	N	GND
28.210000	36.60	11.4	73	36.4	N	GND
29.434000	32.70	11.5	73	40.3	N	GND
29.986000	35.70	11.5	73	37.3	N	GND

The objective of this test is to check the compliance of the equipment to the EN55011 standard. It deals with measuring the conducted disturbance level emitted by power supply conductors, video ports conductors in the frequency band 150 kHz - 30 MHz. Test procedures are defined in the standards EN 55011.

2.3.2 Conducted Emission Limit

Frequency Range (MHz)	Limits (dBuV)
	Quasi-Peak
0.090~0.150	N.A
0.150~0.500	79
0.500~30.000	73

2.3.3 Operating Condition of EUT

EUT is turned on during the test, and the maximum emanating results are recorded.

2.3.4 Test Configuration and Procedure

EUT is placed on a nonmetal table which is 0.8 meter above the grounded reference plane. Connect the lines under testing of the EUT to the LISN which is connected to receiver by coaxial line, then disturbance signals from the lines can be detected by the receiver.

2.4 Test Result


Pass: The overall emission level do not exceed the limits as stated in section 2.3.2

3. Radiated Emission Test

3.1 Test Standards

EN 55011 clause 7

3.2 Diagram of Test Setup




3.3 Test Equipments Used

EQP. Description
All band antenna
R&S EMI Receiver

3.4 Test Description

3.4.1 Configuration of Instruments

Test Receiver Setting



- Detector: Quasi-Peak
- Band Width: 120KHz
- Frequency Range: 30MHz to 1000MHz
- Turntable Rotated: 0 to 360 degrees

Antenna Position:

—Height: 1m to 4m

—Polarity: Horizontal and Vertical

Reported Emission:

EUT: DS-2CD2512XYZ-ABCD

Manufacturer:

Operating Condition:

Test Site: lab 52 EMC Chamber (3m)


Operator: Huang damping

Test Specification:

Comment:

SCAN TABLE: "EN 50121-3-2 F fin"

Start	Stop	Step	Detector	Meas.	IF	Transducer
Frequency	Frequency	Width		Time	Bandw.	
30.0 MHz	1.0 GHz	60.0 kHz	QuasiPeak	1.0 s	120 kHz	CBL 6112B-3



MEASUREMENT RESULT: "3925-1F_fin QP"

10/28/13 8:58PM

Frequency	Level	Transd	Limit	Margin	Height	Azimuth	Polarisation
MHz	dBμV/m		dB	dBμV/m	dB	cm	deg
109.260000	30.40	13.7	50.0	19.6	108.0	191.00	VERTICAL
109.800000	32.40	13.7	50.0	17.6	111.0	295.00	VERTICAL
111.360000	32.70	13.8	50.0	17.3	100.0	186.00	VERTICAL

111.900000	34.50	13.8	50.0	15.5	100.0	315.00	VERTICAL
113.400000	31.80	13.9	50.0	18.2	113.0	194.00	VERTICAL
113.940000	32.60	13.9	50.0	17.4	100.0	329.00	VERTICAL

— Maximum emission configuration was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted.

3.4.2 Radiated Emission Limit

Frequency (MHz)	Distance (Meters)	Field Strengths Limits (dB μ V/m) Quasi-Peak
30 ~ 230	3	50
230 ~ 1000	3	57

Note: (1) The tighter limit shall apply at the edge between two frequency bands.

(2) Distance refers to the distance in meters between the test instrument antenna and the closest point of any part of the E.U.T.

3.4.3 Operating Condition of EUT

The operation mode of EUT is same as Section 2.4.3, except the test setup.

3.4.4 Test Configuration and Procedure

EUT is tested in Semi-Anechoic Chamber. EUT is placed on a nonmetal table which is 0.8 meter above a grounded turntable. The turntable can rotate 360 degrees to determine the azimuth of the maximum emission level. EUT is set 3 meters away from the center of receiving antenna, and the antenna can move up and down from 1 to 4 meter to find out the maximum emission level. Both horizontal and vertical polarizations of the antenna are set on the test

3.5 Test Result

Pass: The overall emission level do not exceed the limits as stated in section 3.4.2.

4. Electrostatic Discharge Test

4.1 Test Standards

IEC 61000-4-2


4.2 Severity Levels and Performance Criterion

4.2.1 Severity level: Contact Discharge at $\pm 6\text{KV}$ Air Discharge at $\pm 8\text{KV}$

Level	Test Voltage Contact Discharge (KV)	Test Voltage Air Discharge (KV)
1	2	2
2	4	4
3	6	8
4	8	15
X	Special	Special

4.2.2 Performance criterion: A

4.3 Diagram of Test Setup



(The 470 k Ω resistors are installed per standard requirement.)

4.4 Test Equipments Used

EQP. Description
ESD Simulator

4.5 Test Description

4.5.1 Operating Condition of EUT:

The EUT is turned on during the test, and the maximum susceptible results are recorded. The data connections of the EUT and the external monitor PC is established, the health status should be received from the EUT through out the testing.

4.5.2 Test Configuration and Procedure:

Air Discharge:


—This test is done on a non-conductive surfaces. The round discharge tip of the Electrostatic Discharge simulator shall be approached as fast as possible then to touch the EUT. After each discharge, the simulator shall be removed from the EUT. The simulator is then re-triggered for a new single discharge and repeated 10 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed

Contact Discharge:

—All the procedure shall be same as air discharge, except using the acute discharge tip. The top end of the Electrostatic Discharge simulator is touch the EUT all the time when the simulator is re-triggered for a new single discharge and repeated 10 times for each pre-selected test point.

Pass and Fail Criteria: Refer to the justification criteria in section 1.5

4.6 Test Setting



4.7 Test Result

Pass: The functions of EUT under test accord with Requirements refer to 1.5.3

5. RF Field Strength Susceptibility Test

5.1 Test Standards

IEC 61000-4-3

5.2 Severity Levels and Performance Criterion

5.2.1 Severity level:


80 MHz to 1000MHz 20V/m

1.4GHz to 2.1GHz 10V/m

2.1GHz to 2.7GHz 5V/m

Modulation : 80% AM (1kHz) for all ranges

5.3 Diagram of Test Setup



5.4 Test Equipment Used

Equipment Description
Signal Generator
AR/Power Amplifier
AR/Power Amplifier
AR/Field Probes

5.5 Test Description

5.5.1 Operating Condition of EUT

The operation mode of EUT is same as Section 4.5.1., except the test setup.

5.5.2 Configuration of Instruments

80 MHz to 1000MHz 20V/m

1.4GHz to 2.1GHz 10V/m

2.1GHz to 2.7GHz 5V/m

Modulation: 80% AM (1kHz) for all ranges


Step Size: 1% of the start and thereafter 1% of the preceding frequency value.

Dwell Time: 2Sec.

5.5.3 Test Configuration and Procedure

1. The EUT and support units were located at the edge of supporting table keep 3 meter away from transmitting antenna, it just the calibrated square area of field uniformity. And the EUT via DVR previewed on monitor which out of the chamber.
2. Adjusting the cables to be exposed to the electromagnetic field as possible.
3. Performing a Radiated Emission Scan in range of 80 to 1000MHz, 1.4GHz to 2.1GHz, 2.1GHz to 2.7GHz prior to do RS test and records the more higher emission frequencies for the reference of RS test, due to antenna effectiveness.
4. Setting the testing parameters of RS test software per IEC 61000-4-3.
5. Referring to the tested data of step 3 to performing the RS test.
6. Check the functions of EUT refer to 1.5.3
7. Changing the EUT to the other side and repeat step 3 to 6, until 4 sides of EUT were verified.
Refer to the justification criteria in section 1.6.1

5.6 Test Setting



5.7 Test Result

Pass: The functions of EUT under test accord with Requirements refer to 1.5.3

6. Electrical Fast Transient/Burst Test

6.1 Test Standards


IEC 61000-4-4 clause 8

6.2 Severity Levels and Performance Criterion

6.2.1 Severity level: ± 2 kV 5/50 ns Tr/Th with 5 kHz repetition frequency, burst duration 15ms, burst period 300ms

Open Circuit Output Test Voltage $\pm 10\%$		
Level	For Power Supply Lines	
	V peak(KV)	Repetition Frequency(KHz)
1	0.5	5
2	1	5
3	2	5
4	4	2.5
x	Special	Special

6.3 Diagram of Test Setup



Ports for testing

Port under testing
Video & Audio output
DC 12V input

6.4 Test Equipment Used

EQP. Description
Fast Transients /Burst Generator

6.5 Test Description

6.5.1 Operating Condition of EUT:

The operation mode of EUT is same as Section 4.5.1., except the test setup.

6.5.2 Test Requirements

EUT and its simulators shall be placed 0.8m high above the ground reference plane which is a minimum 1m*1m with minimum 0.65mm thickness. This reference ground plane shall project beyond the EUT by at least 0.1m on all sides and the minimum distance between EUT and all other conductive structure, except the ground plane beneath the EUT, shall be more than 0.5m.


6.5.3 Test Configuration and Procedure

EUT is connected to coupling/decoupling network which couples the EFT signal to power input and video & audio lines. During the test, both polarities of the test voltage should be applied and the duration of the test can't be less than 1 mins.

Record any performance degradation of the EUT during the test and judge the test result according to the stated performance criterion:

Test Criterion A is applied together with the following requirements refer to the justification criteria in section 1.5

6.6 Test Setting



6.7 Test Result

Pass: The functions of EUT under test accord with Requirements refer to 1.5.3

7. Surge Test

7.1 Test Standards

IEC 61000-4-5 Clause 8

7.2 Severity Levels and Performance Criterion


Open circuit test voltage line to ground:

+/- 2KV 42 Ω , 0.5mF

Open circuit test voltage line to line:

+/-1KV 42 Ω , 0.5mF

7.3 Diagram of Test Setup



7.4 Test Equipment Used

EQP. Description
SURGE SIMULATOR
CDN

7.5 Test Description

7.5.1 Operating Condition of EUT:

The operation mode of EUT is same as Section 4.5.1., except the test setup.

7.5.2 Test Configuration and Procedure

Test Port: DC Power Port

Basic Standard: IEC/EN 61000-4-5

Requirements: ± 2 kV(Line to Ground))

± 1 kV(Line to Line)

Performance Criteria: B.

Tested by : Wei Liu

Temperature : 30C°

Relative Humidity: 43%

Pressure: 1010mbar

Test Procedure

1. The EUT and support units were located on a wooden table 0.8 m away from ground floor.
2. Injected test voltage to the EUT ports from minimum to standard request or client request.
3. Recorded the test result as shown in following table.

C-6-6 Performance and Result

Voltage Waveform: 5/50 us

Current Waveform: 8/20 us


Polarity: Positive/Negative

At least 5 positive and 5 negative (polarity) surge test

Record any performance degradation of the EUT during the test and judge the test result according to the stated performance criterion:

Test Criterion B is applied together with the following requirements refer to the justification criteria in section 1.5

7.6 Test Setting



7.7 Test Result

Pass: The functions of EUT under test accord with Requirements refer to 1.5.3

8. Conducted Susceptibility Test

8.1 Test Standards

IEC 61000-4-6 Clause 8

8.2 Severity Levels and Performance Criterion

8.2.1 Severity Level: 10 Vrms (carrier voltage)


150 kHz to 80 MHz

1 kHz, 80% AM

Source impedance 150Ω

Injection Methods: CDN for all ports

8.3 Diagram of Test Setup



8.4 Test Equipment Used

EQP. Description
SCHAFFNER/RF Generator
CDN

8.5 Test Description

Test Condition

Port: DC Power Port and signal Port

Basic Standard: IEC/EN 61000-4-6

Requirements: 10V, with 80% AM. 1kHz Modulation.

Injection Method: CDN-M2 for DC Power Port

CDN-T4 for signal Port

Performance Criterion: A (Standard Required)

Tested by: Wei Liu

Temperature: 28C°

Humidity: 50%

Pressure: 1010mbar

Frequency Range: 0.15MHz-80MHz

Frequency Step: 1% of fundamental

Dwell Time: 3 sec

1. The EUT and support units were located at a ground reference plane with the interposition of a 0.1 m thickness insulating support and the CDN was located on GRP directly.

Set the testing parameters of CS test software as per IEC/EN 61000-4-6.

Record any performance degradation of the EUT during the test and judge the test result according to the stated performance criterion.:

Test Criterion A is applied together with the following requirements refer to the justification criteria in section 1.5

8.6 Test Setting



8.7 Test Result

Pass: The functions of EUT under test accord with Requirements refer to 1.5.3

9. Power supply over voltage

9.1 Test Standards


EN 50155 12.2.6

Test requirements:

$1.4U_n$, $d=0.1\text{sec}$, $D=1\text{sec}$, $R_s = 1\ \Omega \pm 10\%$

Trapezoidal overvoltage according to EN50155 12.2.6 a)

9.2 Diagram of Test Setup



9.3 Test Configuration and Procedure

The EUT is tested with over voltage with the pulse generated by alternating switching between U_n and $1.4 U_n$ with a pulse controlled relay. Test acceptance requirements:

- No failure shall occur
- No degradation of functions has occurred.

9.4 Test Setting



9.5 Test Result

Pass: No failure occurs and no degradation of functions has occurred.

10. Vibration Test

Base Standard : EN50155 clause 12.2.11

Test Standard : EN 61373

Equipment used in testing : Vibration Table


Random Vibration Test Parameters – 1 (Functional test)

Direction	Frequency (Hz)	ASD level (m/s ²) ² /Hz	RMS value m/s ²
Vertical	5-10	+9dB/octave	5.4
	10-100	0.190	
	100-250	-6 dB/octave	
Transverse	5-10	+9dB/octave	4.7
	10-100	0.144	
	100-250	-6 dB/octave	
Longitudinal	5-10	+9dB/octave	2.5
	10-100	0.0414	
	100-250	-6 dB/octave	
Test Time: 30 mins (Each axis)			

Random Vibration Test Parameters – 2 (Long life test)

Direction	Frequency (Hz)	ASD level (m/s ²) ² /Hz	RMS value m/s ²
Vertical	5-10	+9dB/octave	42.5
	10-100	11.83	
	100-250	-6 dB/octave	
Transverse	5-10	+9dB/octave	37
	10-100	8.96	
	100-250	-6 dB/octave	
Longitudinal	5-10	+9dB/octave	20
	10-100	2.62	
	100-250	-6 dB/octave	
Test Time: 5 hrs (Each axis)			

Definition of vibration axis



10.1 Test Procedure

1. The EUT is securely mounted on the vibration tables with the orientations that coincided with the test axis.

The control accelerometer is located on the fixture for all vibrations tests for monitoring, these data will be send back to the control monitoring software for data logging through out the testing.

2. Start the vibrations test according to Test Parameter -1 and then repeat the test for Test Parameter -2.

10.2 Acceptance Criteria

The functional test requirement is refer to section: 1.5.3

Passing Criteria:

No damage and failure should be found during and after vibration test.

Screws, nuts and other mechanical parts should be securely fixed without loose.

10.3 Test Result

Pass: No damage and failure occurred and the functions of EUT under test accord with Requirements refer to 1.5.3.

11. Shock Test

Base Standard : EN50155 clause 12.2.11

Test Standard : EN 61373

Wave Form : Half sine wave

Acceleration : 300m/s²

Duration Time : 18ms

No of shock : 3 times (Each Axis)

Shock direction : $\pm$ Longitudinal, $\pm$ Transverse, $\pm$ Vertical

11.1 Test Procedure:

1. The EUT is securely mounted on the vibration tables with the orientations that coincided with the test axis.
2. The control accelerometer is located on the fixture for all shock tests for monitoring these data will be send back to the control monitoring software for data logging through out the testing.
3. Start the test and repeat for each axis

11.2 Acceptance Criteria

The functional test requirement is refer to section: 1.5.3

Passing Criteria:

No damage and failure should be found during and after shock test.

Screws, nuts and other mechanical parts should be securely fixed without loose.

11.3 Test Result

Pass: No damage and failure occurred and the functions of EUT under test accord with

Requirements refer to 1.5.3.

12. Dry Heat Test

Base Standard: EN50155 clause 12.2.4

Test Standard: EN 60068-2-2

12.1 Test Procedures

1. Perform function test (Refer to section 1.5.3.)
2. Place sample to chamber at 25'C.
3. Ramp up temperature to 70'C in 45min
4. Maintain temperature at 70'C for 8 hours
5. Perform function test
6. Ramp down to 25'C in 30min
7. Perform function test (Refer to section 1.5.3.)

12.2 Acceptance Criteria


The functional test requirement is refer to section: 1.5.3

Passing Criteria:

No damage and failure should be found during and after shock test.

Screws, nuts and other mechanical parts should be securely fixed without loose.

12.3 Test Setting



12.4 Test Result

Pass: No damage and failure occurred and the functions of EUT under test accord with Requirements refer to 1.5.3.

13. Cooling Test

Base Standard: EN50155 clause 12.2.3

Test Standard: EN 60068-2-1

13.1 Test Procedures

1. Perform function test (Refer to section 1.5.3.)
2. Place sample to chamber at 25°C.
3. To lower the temperature to -25°C in 50min
4. Maintain temperature at -25°C for 2 hours, then switch the sample on and a performance check is carried out, keeping the equipment at the low temperature for 8 hours.
5. Ramp down to 25°C in 30min
6. Perform function test (Refer to section 1.5.3.)

13.2 Acceptance Criteria


The functional test requirement is refer to section: 1.5.3

Passing Criteria:

No damage and failure should be found during and after shock test.

Screws, nuts and other mechanical parts should be securely fixed without loose.

13.3 Test Setting



13.4 Test Result

Pass: No damage and failure occurred and the functions of EUT under test accord with Requirements refer to 1.5.3.

NOTES

1. Reports with no signet of "test report" or that of the inspect institute are all invalid.
2. Partial copy of this report is forbidden. Entire copy of the report without signet is invalid.
3. Report with no approval are invalid.
4. Altered report is invalid.
5. If any disagreement on this report, a written claim is requested to be submit to the institute within 15days on receipt of the report.
6. Generally, authorized inspection is only responsible for the samples inspected.

Address: 36#, Macheng Road, Hangzhou, China

Tel: +86 571 88366802 +86 571 88828284

Fax: +86 571 88366821

P.O.Box: 1215#, Hangzhou, China

Zip Code: 310012

E-mail: wwx@chinacptc.net

WEB: www.chinacptc.net