

2 Wire HD Video Intercom Solution Release Note (2023-12-15)


Device Model	Firmware Version
DS-KD7003EY-IME2	VIS_OUTDOOR_F2pro_EN_STD_V1.0.2_build231208
DS-KH7300EY-TE2 DS-KH7300EY-WTE2	VIS_INDOOR_B1pro_EN_STD_V2.2.32_build231012
DS-KD-TDM DS-KD-TDE	VIS_KDDIS_R0_EN_STD_V1.0.1_231008

Reason of Upgrade


Add new feature, fix bugs, enhance products quality and meet customers' requirements.

Modified Features

- Compatible with new released 12 key nametag module DS-KD-K12 and DS-KD-K12/S



- Update the default button No. (room number) image.



2 Wire HD Video Intercom Solution Release Note (2023-10-25)

Device Model	Firmware Version
DS-KD7003EY-IME2	VIS_OUTDOOR_F2pro_EN_STD_V1.0.1_build231019
DS-KH7300EY-TE2 DS-KH7300EY-WTE2	VIS_INDOOR_B1pro_EN_STD_V2.2.32_build231012
DS-KD-TDM DS-KD-TDE	VIS_KDDIS_R0_EN_STD_V1.0.1_231008

Reason of Upgrade

Fix bugs, enhance products quality and meet customers' requirements.

Modified Features


3. Optimize Italian language translation in mobile phone web interface

2 Wire HD Video Intercom Solution Release Note (2023-10-16)

Device Model	Firmware Version
DS-KD7003EY-IME2	VIS_OUTDOOR_F2pro_EN_STD_V1.0.1_build231012
DS-KH7300EY-TE2 DS-KH7300EY-WTE2	VIS_INDOOR_B1pro_EN_STD_V2.2.32_build231012
DS-KD-TDM DS-KD-TDE	VIS_KDDIS_R0_EN_STD_V1.0.1_231008

Reason of Upgrade

Video intercom 2-Wire HD solution first time released.



New Features

Door Station-KD7003 main module

- Excellent Product Design: HD images and wide viewing angle (Horizontal: 133°, Vertical: 82°) with WDR
- Excellent Product Design: IP65&IK08 protection level, compatible with released sub-modules (DIS is not supported for now)
- Easy to Use: Support mobile web configuration (AP mode)
- Easy to Use: DEC knobs configuration, Plug & play
- Easy to Use: Multiple indicators--Opening door, calling, on call, in use
- Easy to Use: Single and double buttons can be freely adjusted
- Supports two-lock control (lock1 for pulse lock, lock2 for magnetic/door strike/electric bolt)

Capacity:

User capacity: 2000

Linked indoor station capacity: Max.99

Sub door station capacity: 16

Indoor Station-KH7300

- Excellent Product Design: 7-inch touch screen with 1024*600 high resolution
- Excellent Product Design: 3 touch buttons, physically challenged friendly
- Easy to Use: DEC knobs configuration;
- Easy to Use: Plug & play, support different connection topologies
- Easy to Use: Supports Hik-Connect App (model with W only)
- Easy to Use: Multiple indicators--Wi-Fi, power, mute, in use
- Easy to Use: Max. 4 custom virtual buttons
- View live image of door stations

- Support Professional Studio / Trade button function (Open doors automatically)
- Supports Floor Call (trigger alarm input and indoor station will prompt with audio)

For more information about 2 wire HD products, please refer to the QSG and user manual of device on website:

<https://www.hikvision.com/en/products/Video-Intercom-Products/2-wire-Series/2-wire-hd/?category=Video+Intercom+&subCategory=2-Wire+Series&series=2+Wire+HD&checkedSubSeries=NONE>

Customer Impact and Recommended Action

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action.

For any questions and request for this firmware, please contact our local technical support team.

Note:

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain errors known as errata, which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd.
No. 555 Qianmo Road, Binjiang District, Hangzhou 310051,
China
Tel: +86-571-8807-5998
FAX: +86-571-8993-5635
Email: overseabusiness@hikvision.com