2019-1033 page 1 of 7

No: 2019-1033



中国认可 检测 TESTING CNAS L046



TEST

REPORT

Equipment under Test: Network camera

Model Number: DS-2XM6222FWD-IM

Manufacturer: Hangzhou Hikvision Digital Technology Co., Ltd

National Computer Peripheral Equipment Quality
Supervising Test Center

National Computer Peripheral Equipment Quality Supervising Test Center

Test Report

No:2019-1033

N <u>o</u> :2019-1033					
		Model type	DS-2XM6222FWD-IM		
Product	Network camera	Trademark	HIKVISION		
Entrusted By	Hangzhou Hikvision Digital Technology Co., Ltd	Testing Type	Entrustment		
Manufacturer	Hangzhou Hikvision Digital Technology Co., Ltd	Sample Class			
Sample Origin	Delivered	Delivery Date	2019-01-14		
Sample Number	One set	Delivered by	Su Weijie		
Sample Radix		Manufacture Date			
Test Standards	IEC 60529: 2013 Degrees of protection provided by enclosures(IP Code)				
Test Items	1#: IP Code 67 test of protection				
Test Result	This test proved that to manufactured by Hangzhou Hikk the Test Standard.	vision Digital Tech			
Remark	The manufacturer declares to DS-2XM6212FWD-IM, D	212FWD-I and the	e test DS-2XM6222FWD-IM		

Approved by: Approved by: Checked by: Chief tester: Keve

Test Site	National Computer Peripheral Equipment Quality Supervising Test Center						
Test Date	2019-01-15~01-16						
	S/N	Description	Model	No.	Cal due		
	1	Water jet hose nozzle	HY-IPX1-6	SB116	2019-04-19		
Main	2	Dust Chamber	SC-500	HJ0083	2019-04-09		
Testing Equipments and Instruments							
motrumonto							
Sample Number	1#: 213	3442819					
Distribution Of Sample	1#: IP (Code 67 test of protection					
Remark	Ambier Relative	c conditions: nt temperature: 25°C e humidity: 55% oheric pressure: 101.2kPa					

page 4 of 7

Test Items	Technical specifications	
root nome		1#
IP6X	Dust-tight, No ingress of dust. The test is performed using a dust chamber. The talcum powder used shall be able to pass through a square-meshed sieve the nominal wire diameter of which is 50 µm and the nominal width of a gap between wires 75 µm. The amount of talcum powder to be used is 2 kg per cubic metre of the test chamber volume. Duration of test: 8 hours. After the test, the inside of EUT should be no dust.	
IPX7	Diving tests for a short time, No ingress of water. -The test is made using a water tank. -Temperature of the water tank: 20℃ -Samples from the bottom of the water: 1000mm -Duration of test: 30 minutes After test, the inside of EUT should be no water.	
Remark		

Tester: Shen Jianjun Wang Jue

page 5 of 7

EUT picture





|福康|| 一致 | 近外 | 网络 | 資 | 銀 | 4 | 105 | 2018

DS-2XM6222FWD-IM 12mm

5.2W MAX / PoE(802.3af)

序列号: 213442819

V5.5.0_170914

产品执行标准: 0/BFW 006-2015

杭州海康威搜数字技术股份有限公司



2019-1033 page 6 of 7

Test picture



During the test (IP6X)



During the test (IPX7)

NOTES

- 1. Reports with no signet of "test report" or that of the inspect institute are all invalid.
- 2. Partial copy of this report is forbidden. Entire copy of the report without signet is invalid.
- 3. Report with no approval are invalid.
- 4. Altered report is invalid.
- 5. If any disagreement on this report, a written claim is requested to be submit to the institute within 15days on receipt of the report.
- 6. Generally, authorized inspection is only responsible for the samples inspected.

Address: 316#, Jiang Hong South Road, Hangzhou, China

Tel: +86 571 88278723 +86 571 88828284

Fax: +86 571 88366821

P.O.Box: 1215#, Hangzhou, China

Zip Code: 310052 E-mail: wangwx@ksign.cn WEB: www.ksign.cn